

Repeaters and Distribution

4K HDMI Distribution Amplifier 1x4**VP-840**

| | |
|-----------------------|--|
| Video Input/Output | Input: 1 x HDMI Output: 4 x HDMI |
| Video Format | <p>HDMI Supported Resolutions 4096x2160p60/59.94/50 4096x2160p30/29.97/25/24/23.98 3840x2160p60/59.94/50 3840x2160p30/29.97/25/24/23.98 1080p60/59.94/50, 1080p30/29.97/25/24/23.98 1080i60/59.94/50, , 720p60/59.94/50 480p, 576p, 480i, 576i</p> <p>PC Supported Resolutions 640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1280x720@60Hz, , 1280x768@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@ 60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1680x1200@60Hz, 1920x1080@60Hz, 1920x1200@60Hz</p> |
| Video Standard | ---- |
| Video Processing | HDR 4K2K@60 4:2:0 10bits 4K2K 60Hz YCbCr4:4:4 8bit/YCbCr4:2:0 10bit 4K2K 30Hz YCbCr4:4:4 8bit |
| Video bandwidth | Single-link 600MHz (18Gbps) |
| Audio Format | DTS-HD Master Audio, Dolby TrueHD, Dolby Digital, DTS, DVD-Audio, LPCM, SACD, MPCM |
| Power | 12V / 6W |
| Dimension (LxWxH) | 174 x 63 x 35 mm |
| Weight | 0.35 kg |
| Operating Temp. Range | 0~40 °C |
| What's in the Box | 1 x VP-840 product 1 x AD Switch DC 12V |